
MAFI Representatives


MAFI has a worldwide network of representatives to support you in your procurement, service and maintenance tasks.



represented by	
renresenten nv	
cpicaciited by	

MAFI Transport-Systeme GmbH

Hochhäuser Straße 18 97941 Tauberbischofsheim Germany **3** +49 9341/899-0



www.mafi.de

Disclaimer

The models shown here may include different configurations, dimensions, weights and services that are not available in certain countries or may vary depending on the version. The equipment shown or mentioned may be part of special equipment (e.g. options and accessories) and may vary depending on local regulations. We would be pleased to provide you with further information. The colour representation may vary slightly due to printing or presentation. We also reserve the right to make changes, typesetting errors and printing errors. Furthermore, we reserve the right to change the technical details listed here without prior notice.

Text, images, graphics and their arrangement are protected by copyright and other protective rights. The content presented here may not be copied, distributed, changed or made accessible to third parties for commercial purposes. We would like to point out that the text, images and graphics contained herein are wholly or partly subject to the copyright of third parties. Unless otherwise indicated, all trademarks used herein are protected under trademark laws. This applies in particular to brands, type designations, logos and emblems.



T 230e





Version: 11 / 2023 English mafi.de



Vehicle type T 230e

Operating areas Seaports, Distribution-/Logistic Centers, Industry

System load (GCWR) approx. 90,000 kg

Vehicle drive/Motor ZF Cetrax electric central drive, max. output 300 kW

Battery pack Lithium-ion batteries, 600 V, up to 428 Ah, up to 256 kWh

Charging connector CCS 2.0

Charger DC charger

Dead weight approx. 10,000 kg

Fifth wheel boom Fifth wheel plate Eurohitch 2" FW 3510-TR for 36,000 kg

Lifting capacity approx. 34,000 kg

Wheel base 3,070 mm

Speed up to 40 km/h

Axles front axle (VOLVO), rear axle (Kessler)

Cabin ROPS and FOPS certified, with one side door, access via the platform,

windshield and rear window made of laminated glass,

A/C and heating system

Please see our technical data sheet for more information

MAFI T 230e

Your Electric Terminal Tractor For Container Terminal And Distribution Center Operations

The electric terminal tractor was originally designed for container handling in seaports; however, it can also be used in many industrial applications that involve moving heavy loads.

It exceeds the strictest requirements in terms of handling, comfort and productivity.

Furthermore, this tractor has the advantage of low operating costs over its entire service life.

Built to current technical standards, this generation of terminal tractors is state-of-the-art and includes many important benefits and improvements for operators, workshops, drivers, as well as the environment.







